




## INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

<p>(51) International Patent Classification <sup>7</sup> : <b>H04Q 7/38, 7/22</b></p>	<p><b>A1</b></p>	<p>(11) International Publication Number: <b>WO 00/35226</b></p> <p>(43) International Publication Date: 15 June 2000 (15.06.00)</p>
<p>(21) International Application Number: <b>PCT/EP98/07932</b></p> <p>(22) International Filing Date: 7 December 1998 (07.12.98)</p> <p>(71) Applicant (for all designated States except US): <b>NOKIA NETWORKS OY [FI/FI]; P.O. Box 300, FIN-00045 Nokia Group (FI).</b></p> <p>(72) Inventor; and (75) Inventor/Applicant (for US only): <b>LONGONI, Fabio [FI/FI]; Visamäki 5 E 38, FIN-02130 Espoo (FI).</b></p> <p>(74) Agent: <b>PELLMANN, Hans-Bernd; Tiedtke-Bühling-Kinne, Bavariaring 4, D-80336 München (DE).</b></p>		<p>(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).</p> <p><b>Published</b> With international search report.</p>

(54) Title: CELL LOAD CONTROL METHOD AND SYSTEM

## (57) Abstract

A method and system for performing cell load control in a mobile radio network using diversity connections between base stations is described, wherein the efficiency of the resource management in the radio network is improved by transmitting an external message containing a load information of a cell to a radio network controller not serving this cell. The transmission may be performed in response to a corresponding request transmitted by the radio network controller to another radio network controller which serves the corresponding radio cell. When the radio network controller has received the load information of the cell controlled by the other radio network controller, it may use the load information for deciding on a load status of the radio cell. Thereby, the resource management of radio network is more efficient and the load is maintained balanced among different cells, wherein a possible situation of cell congestion and high interference is avoided. Moreover, the active set management efficiency is improved, resulting in a higher connection quality, since the decision algorithm to change the active set is faster and more efficient. (Fig. 3)



**FOR THE PURPOSES OF INFORMATION ONLY**

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

**Cell load control method and system**FIELD OF THE INVENTION

5

The present invention relates to a method and system for performing cell load control in a mobile radio network using diversity connections between base stations, such as a radio access network of a WCDMA (Wideband Code Division  
10 Multiple Access) system like the UTMS (Universal Mobile Telecommunications System).

BACKGROUND OF THE INVENTION

15 In a radio access network of a WCDMA system, a soft handover is an essential feature which allows an efficient use of the capacity which can be offered by network. In a soft handover state, one mobile station (MS) is connected using a plurality of radio cells contained in its active set (AS)  
20 as a resource. The MS monitors levels of received signals broadcasted from neighboring base stations, compares them to a set of thresholds, and reports the measurement of neighbor cells to a radio network controller (RNC) controlling this specific MS, i.e. a Serving RNC (SRNC), and, using  
25 this information, the SRNC may transmit a command to the MS to add a new radio cell to its active set, delete a radio cell, replace one or more radio cells, perform an interfrequency handover, and so on. The active set is defined as a set of base stations from which the same user information  
30 tion is sent, simultaneously demodulated and coherently combined.

However, a problem arises when the new or "candidate" cell to be added to the active set is not controlled by the SRNC (such a cell is referred to as "drift cell"), because the load or congestion status of that cell is not available at  
5 the SRNC.

Another problem arises when the drift cell is already in the active set, i.e. radio cells which are actively used in the present connection of the MS (inter RCN soft handover).  
10 Also in this case, the load status of the drift cell is not known to the SRNC and cannot be considered when the SRNC decides on the execution of a handover, i.e. a handover for traffic reasons is not possible.

15 A simple solution to the above problems is that the SRNC ignores the load status of the drift cell, and the load status is not used in the decision to add this drift cell to the respective set of the MS. In contrast thereto, the load status of the cells controlled by the SRNC is available and can be used by a handover algorithm performed in  
20 the SRNC. When the SRNC decides to add the drift cell to the active set solely on the basis of the measurement report, it transmits a dedicated message (branch addition request) to the so-called Drift RNC (DRNC) controlling the  
25 drift cell, wherein the DRNC decides whether to accept or reject the addition of the new cell on the basis of the cell load status (admission control procedure).

However, the load of the drift cell cannot be checked by  
30 the SRNC, even if the cell is in the active set of the MS controlled by the SRNC. Thus, the radio resource management (RRM) algorithm such as a handover control algorithm of the SRNC cannot be used in an efficient manner, because the

load of the drift cell is not known. This leads to the following specific problems:

- 1) The SRNC may decide to add the drift cell to the active set even if the load of the cell is high and some other radio cells of less load could have been selected. Accordingly, the SRNC sends a branch addition message to the DRNC which may accept the new cell, wherein the increased load of the accepted radio cell may cause an increased interference such that the distribution of the load in the network is not balanced. Otherwise, the DRNC may refuse the new radio cell (branch), wherein the SRNC decides on the following step in accordance with its control algorithms, which causes a delay due to the external signaling between the SRNC and the DRNC. In a worst case scenario, the SRNC may try a view moments later to add the same radio cell to the active set to another or even the same MS.  
  
2) The load of a drift cell already included in the active set of the MS may increase. Since the drift cell is not controlled by the SRNC, the SRNC is not aware of the load increase, which may lead to an unbalanced network. Moreover, the load of the cell may increase to such an extent that the cell reaches a congestion state, and the branch is lost or deleted by the DRNC. Thereby, the quality of the connection may decrease.  
  
3) The SRNC may request to add a drift cell which is not available due to a congestion status or a hardware failure to the active set of the controlled MS. Again, this might lead to a decrease in the quality of the connection.

SUMMARY OF THE INVENTION

- 5 It is therefore an object of the present invention to provide a method and system for performing a cell load control, which enable a more efficient use of the radio resource algorithms and thus of the system capacity.
- 10 This object is achieved by a method for performing cell load control in a mobile radio network using diversity connections between base stations, comprising the steps of: transmitting a load information of a radio cell from a first radio network controller serving a radio cell to a  
15 second radio network controller not serving the radio cell; and  
using the load information in the second radio network controller for deciding on a load status of the radio cell.
- 20 Additionally, the above object is achieved by a system for performing a cell load control in a mobile radio network using diversity connections between base stations, comprising:  
a first radio network controller comprising transmitting  
25 means arranged for transmitting a load information of a radio cell served by the first radio network controller to a second radio network controller not serving the radio cell; and  
the second radio network controller comprising a receiving  
30 means arranged for receiving the load information, and a decision means arranged for deciding on a load status of the radio cell.

Accordingly, since the second radio network controller thus knows the load status or condition of the drift cell controlled by the first radio network controller, it can use its radio resource algorithms in a more effective way.

5

The decision on the load status of the radio cell can be used for deciding on an admission of the radio cell for handover of a mobile terminal controlled by the second radio network controller. Thus, the second radio network controller may refer to the received load information, in case an admission decision concerning a drift cell has to be made. The admission control is then able to check whether the drift cell has sufficient resources to accept a new branch.

15

Thereby, the system capacity can be used more efficiently and the active set management and thus the overall quality of the connections are improved.

20 Since the benefits of the present invention depend on the probability to have a drift cell contained in the active set of a MS, the advantage achieved by the present invention is high in case of small controlling areas of the radio network controller, or in case the SRNC relocation is never triggered (anchor RNC concept) or rarely triggered.

25

Moreover, a high advantage can be achieved, if the radio network is planned in such a way that radio cells controlled by different radio network controllers are mixed together in the same area, which may be the case when an operator decides to expand the network using equipment from another vendor, i.e. multivendor scenario without an open Iub interface.

30

Preferably, the load information is transmitted in response to a load request issued by the second radio network controller. Thus, the second radio network controller may issue a load request, in case a drift cell is included in the active set of a controlled MS. Thereby, the signaling load due to the transmission of the load information can be restricted to those cases where the load information is actually required by the SRNC.

10

Furthermore, the load information can be transmitted when a load level of the radio cell has reached a predetermined load threshold. Thereby, an addition of a congested cell to the active set of the MS can be prevented, since the SRNC is informed by the transmitted load information. In this case, the second radio network controller may command a controlled MS to replace or delete a branch to the congested radio cell, in response to the load information. Thus, the loss of a branch due to the use of a congested radio cell can be prevented.

20

Furthermore, the second radio network controller may issue the load request on the basis of a measurement of neighbor cells reported by the mobile terminal. Thus, the second radio network controller may issue the load request only for potential candidate cells to be added to the active set of the mobile terminal.

25

Moreover, the load request may be issued when the radio cell is included in an active set or a candidate set of the mobile terminal, wherein the active set or the candidate set is used for determining radio cells for the handover of the mobile terminal.

30

Additionally, the load request may be issued when the mobile terminal has transmitted a request to the second radio network controller to add the radio cell to the active set.  
5 Thereby, the second radio network controller may check the received load information before deciding on the admission of the drift cell.

Preferably, a periodical load information may be requested  
10 by the load request. By means of the periodical load report, the second radio network controller may monitor the load status of a drift cell included in the active set of the mobile terminal, such that the signaling load due to continued load requests can be reduced.

15 Preferably, the load information includes a transmission power level and a received interference level of the radio cell. Accordingly, the second radio network controller may compare the receive transmission power level and interference level with a maximum transmission power level and a  
20 maximum reception interference level to thereby evaluate the load status of the drift cell.

The first radio network controller may comprise a determination means for determining a load level of the radio cell  
25 and for generating the load information. Preferably, the determination means controls the transmitting means so as to transmit the load information, when the load level of the radio cell has reached the predetermined load threshold.  
30 old.

Furthermore, the first radio network controller may comprise a receiving means for receiving a load request trans-

mitted by a transmitting means of the second radio network controller, wherein the determination means is arranged to control the transmitting means of the first radio network controller to transmit the controlled information, when the  
5 load request has been received by the receiving means.

Furthermore, the determination means may be arranged to periodically determine the load information and to control the transmitting means of the first radio network controller to periodically transmit the load information.  
10

Preferably, the determination means is arranged to determine the load information on the basis of a load parameter received by the first radio network controller from a base  
15 station of the radio cell.

As an alternative, the load status can be used for deciding on an amount of capacity which can be allocated to a user.

20 As a further alternative, the load status can be used for deciding when to order a mobile terminal to switch to a dedicated channel state. In this case, the mobile terminal may be ordered to switch to said dedicated channel, when the load status indicates an overload of a common channel.  
25

#### BRIEF DESCRIPTION OF THE DRAWINGS

In the following, the present invention will be described  
30 in greater detail on the basis of a preferred embodiment with reference to the accompanying drawings, in which:

Fig. 1 shows a principle block diagram of a radio access network of the UMTS, in which the preferred embodiment of the present invention may be implemented,

5 Fig. 2 shows a principle block diagram of a radio access network in which two adjacent radio cells are served by a cell load control system according to the preferred embodiment of the present invention, and

10 Fig. 3 shows a flow diagram of cell load control procedure according to the preferred embodiment of the present invention.

15 DESCRIPTION OF THE PREFERRED EMBODIMENT

In the following, the preferred embodiment of the method and system according to the present invention will be described on the basis of a radio access system of the UMTS,  
20 as shown in Fig. 1.

According to Fig. 1, a UTRAN 4 is connected to a GPRS-based core network and to a GSM-based core network. Furthermore, a mobile station (MS) 1 is radio-connected to at least one  
25 base station (BS) 2 which is connected to a radio network controller (RNC) 3 of the UTRAN 4. In WCDMA-based systems, the MS 1 can be connected to several BS 2 simultaneously due to macrodiversity.

30 The RNC 3 is connected to a mobile switching center (MSC) 5 of the UMTS which provides access to a circuit switched network such as a public switched telephone network (PSTN) 8 or to a packet-switched network such as the Internet 9.

Additionally, the RNC 3 is connected to a Serving GPRS Support Node (SGSN) 6 of the UMTS. The SGSN 6 is connected to a Gateway GPRS Support Node (GGSN) 7 which provides access to the Internet 9.

The RNC 3 performs radio network control functions such as a connection establishment and release, handover, power control and radio resource handling functions. Diversity combining devices used at soft handover, and a code function are also located in the RNC 3.

The RNC 3 may be built on a generic ATM switch, wherein all devices and a processor are connected to the ATM switch. In the present case, several BS 2 are connected to the RNC 3.

Fig. 2 shows a principle block diagram comprising a first RNC 3-1 and a second RNC 3-2, which serve adjacent radio cells 13 and 23, respectively. The first RNC 3-1 is connected via the MSC 5 to the second RNC 3-2, wherein the second RNC 3-2 serves the corresponding radio cell 23 via a base station (BS) 2-2. Furthermore, the first RNC 3-1 serves the corresponding radio cell 13 via another BS 2-1.

It is noted that the first and second RNC 3-1, 3-2 are also connected to other BSs (not shown) so as to serve a plurality of respective radio cells.

In the case shown in Fig. 2, a mobile station (MS) 1 is located in the radio cell 23 controlled by the BS 2-2 connected to the second RNC 3-2. Thus, the MS 1 is located in the service area of the second RNC 3-2, such that the second RNC 3-2 is the SRNC of the MS 1.

According to the preferred embodiment, the second RNC 3-2 comprises a transceiver 22 for transmitting a request to the first RNC 3-1 to transmit a load information of the radio cell 13 controlled by the first RNC 3-1. Transmissions  
5 between the first RNC 3-1 and the second RNC 3-2 are performed via the MSC 5.

In particular, the second RNC 3-2 may request to transmit  
10 the load information only once, or to transmit a periodical report, i.e. the load information is transmitted every predetermined number of seconds. Moreover, the load information can be transmitted, when the first RNC 3-1 determines a considerable change of the load of the controlled radio  
15 cell 13, e.g. when a critical threshold is reached.

Furthermore, the second RNC 3-2 may request the load information in case the MS 1 has the radio cell 13, which is controlled by the first RNC 3-1, in its active or candidate  
20 set used for a soft handover, or simply because the radio cell 13 controlled by the first RNC 3-1 is a neighbor to the serving area of the second RNC 3-2 and most likely to be added to the active set of the MS 1.

25 The first RNC 3-1 comprises a transceiver 10 arranged for transmitting the load information message to the second RNC 3-2 in response to the receipt of the load request from the second RNC 3-2.

30 The load information message contains load parameters of one (or more) of the radio cells served by the first RNC 3-1. Such load parameters may comprise a transmission power level and a received interference level obtained from the

BS 2-1 connected to the first RNC 3-1. Moreover, the load parameters may comprise a maximum transmission power and a maximum acceptable reception interference level used to determine the load status of the corresponding radio cell 13.  
5 Alternatively, the maximum transmission power and the maximum acceptable reception interference level might be stored in each RNC such that it does not have to be included in the load information message.

10 The first RNC 3-1 comprises a determination means 11 which could be a CPU or the like and which determines a load level of the controlled radio cell 13 based on an information received from the corresponding BS 2-1, and generates the load information message to be supplied to the trans-  
15 ceiver 10. Subsequently, the determination means 11 controls the transceiver 10 so as to transmit the load information message via the MSC 5 to the second RNC 3-2.

Furthermore, the first RNC 3-1 may transmit the load information message concerning its controlled radio cell 13 to  
20 the second RNC 3-2 without any load request from the second RNC 3-2. This could be the case, if the cell served by the first RNC 3-2 is in congestion and cannot accept any new branch. Then, the second RNC 3-2 may transmit a command to  
25 an MS having this radio cell 13 on its active or candidate set to replace or delete that branch.

The load information about the load of the radio cell 13 controlled by the first RNC 3-1 is supplied to a decision  
30 means 21 of the second RNC 3-2. The decision means 21 may be a CPU or the like, and uses the received load information for making a decision as to the admission or deletion

of the corresponding radio cell 13 in the active set of the MS 1 controlled by the second RNC 3-2.

Fig. 3 shows a cell load control procedure performed in the second RNC 3-2, according to the preferred embodiment of the present invention.

According to Fig. 3, the second RNC 3-2 receives a measurement report from the MS 1 via the transceiver 22 (step S101). The received measurement report is supplied to the decision means 21 which determines a candidate cell which might be added to the active set of the MS 1, on the basis of the measurement report (step S102).

Thereafter, the decision means 21 checks whether or not the determined candidate cell is a drift cell (step S103), i.e. a radio cell not served by the second RNC 3-2.

In case the determined candidate cell is not a drift cell, the procedure is continued at step S106, since the load information of the candidate cell is already available at the second RNC 3-2.

In case the determined candidate cell is a drift cell, the decision means 21 controls the transceiver 22 so as to transmit a load request message via the MSC 5 to the transceiver 10 of the first RNC 3-1 (step S104). Then, the second RNC 3-2 waits for the receipt of the load information of the drift cell from the first RNC 3-1.

After the receipt of the load information, the procedure continues at step S106. In step S106, the load status of

the candidate cell is checked in the decision means 21. Based on the load status of the candidate cell, the allowance of the candidate cell to be added to the active set of the MS 1 is decided by the decision means 21 (step S107).

5

Finally, a control command is generated by the decision means 21 based on the decision result and the decision means 21 subsequently controls the transceiver 22 to transmit the control command to the MS 1 (step S108). The control command is a command for the admission or deletion of the candidate cell in the active set of the MS 1.

In addition to the above procedure according to Fig. 3, a control procedure may be provided so as to transmit a control command to the MS 1 to replace or delete a specific branch from the active set, in case a load information indicating a predetermined load threshold or congestion of the branch has been received from the first RNC 3-1 or another RNC without a corresponding request from the second RNC 3-2. Moreover, a dedicated signaling from the DRNC serving a drift cell may be performed to thereby request a removal or modification of branches for load reasons.

However, the cell load control method and system according to the present invention may as well be applied to the following other radio resource allocation cases which differ from the above described handover case.

For example, in case of packet scheduling, an uplink and/or downlink capacity is allocated for a short time period to an NRT (Non-Real Time) data transmission. Therefore, the second RNC 3-2, i.e. the SRNC, needs to know whether and how much capacity can be provided by a drift cell. This

load information can be transmitted in the above described manner from the first RNC 3-1 to the second RNC 3-2 which subsequently decides on the load status of the drift cell 13 and allocates the provided capacity to a requesting user, i.e. a user having transmission data in a corresponding buffer. Thus, the difference with respect to the above handover case lies in the additional determination of the capacity amount to be allocated to the requesting user.

10 An additional example is a common channel (CCH) load control. In this case, the second RNC 3-2 needs to know the load of a common channel, i.e. Random Access channel RACH, Fast Associated channel FACH or Downlink shared channel DSCH, in the drift cell 13, in order to determine when to  
15 order the MS 1 to switch to a dedicated channel (DCH) state due to a load status indicating an overload of the respective common channels.

It is to be pointed out that the cell load control method and system described in the preferred embodiment can be applied in any WCDMA radio access network and basically in all radio networks using diversity connections between base stations controlled by different controllers. The above description of the preferred embodiment and the accompanying  
20 drawings are only intended to illustrate the present invention. The preferred embodiment of the invention may thus vary within the scope of the attached claims.

In summary, a method and system for performing cell load control in a mobile radio network using diversity connections between base stations is described, wherein the efficiency of the resource management in the radio network is improved by transmitting an external message containing a  
30

load information of a cell to a radio network controller not serving this cell. The transmission may be performed in response to a corresponding request transmitted by the radio network controller to another radio network controller which serves the corresponding radio cell. When the radio network controller has received the load information of the cell controlled by the other radio network controller, it may use the load information for deciding on a load status of the radio cell. Thereby, the resource management of radio network is more efficient and the load is maintained balanced among different cells, wherein a possible situation of cell congestion and high interference is avoided. Moreover, the active set management efficiency is improved, resulting in a higher connection quality, since the decision algorithm to change the active set is faster and more efficient.

**Claims**

1. A method for performing cell load control in a mobile radio network using diversity connections between base stations, comprising the steps of:
  - a) transmitting a load information of a radio cell from a first radio network controller serving said radio cell to a second radio network controller not serving said radio cell; and
  - 10 b) using said load information in said second radio network controller for deciding on a load status of said radio cell.
2. A method according to claim 1, wherein said load status is used for deciding on an admission of said radio cell for handover of a mobile terminal controlled by the second radio network controller.
3. A method according to claim 2, wherein said load information is transmitted in response to a load request issued by said second radio network controller.
4. A method according to any one of claims 1 to 3, wherein said load information is transmitted, when a load level of said radio cell has reached a predetermined load threshold.
5. A method according to claim 4, wherein said second radio network controller commands a controlled mobile terminal to replace or delete a branch to said second cell, in response to said load information.

6. A method according to claim 3, wherein said load request is issued on the basis of a measurement of a neighbor cell supported by said mobile terminal.

5 7. A method according to claim 3 or 6, wherein said load request is issued, when said radio cell is included in an active set or a candidate set of said mobile terminal, said active set or candidate set being used for determining radio cells for the handover of said mobile terminal.

10

8. A method according to claim 7, wherein said load request is issued, when said mobile terminal has transmitted a request to said second radio network controller to add said radio cell to said active set.

15

9. A method according to claim 7 or 8, wherein said admission decision is directed to an admission or deletion of said radio cell in the active set of said mobile terminal.

20 10. A method according to claim 3, wherein a periodical load information is transmitted in response to said load request.

11. A method according to any one of the preceding claims,  
25 wherein said radio cell is located adjacent to an area served by said second network controller.

12. A method according to any one of the preceding claims,  
wherein said load information includes a transmission power  
30 level and a received interference level of said radio cell.

13. A method according to any one of the preceding claims, wherein said mobile radio network is a radio access network of the UMTS.

5 14. A method according to claim 1, wherein said load status is used for deciding on an amount of capacity which can be allocated to a user.

10 15. A method according to claim 1, wherein said load status is used for deciding when to order a mobile terminal to switch to a dedicated channel state.

15 16. A method according to claim 15, wherein said mobile terminal is ordered to switch to said dedicated channel, when said load status indicates an overload of a common channel.

20 17. A system for performing cell load control in a mobile radio network using diversity connections between base stations (2-1, 2-2), comprising:

a) a first radio network controller (3-1) comprising transmitting means (10) arranged for transmitting a load information of a radio cell (13) served by said first radio network controller (3-1) to a second radio network controller (3-2) not serving said radio cell (13); and

25 b) said second radio network controller (3-2) comprising a receiving means (20) arranged for receiving said load information, and a decision means (21) arranged for deciding on a load status of said radio cell (13).

30

18. A system according to claim 17, wherein said load status is used for deciding on an admission of said radio

cell (13) for a handover of a mobile terminal (1) controlled by said second radio network controller (3-2).

19. A system according to claim 17 or 18, wherein said  
5 first radio network controller (3-1) comprises a determination means (11) for determining a load level of said radio cell (13) and for generating said load information.

20. A system according to claim 19, wherein said determination  
10 means (11) controls said transmitting means (10) so as to transmit said load information, when the load level of said radio cell (13) has reached a predetermined load threshold.

21. A system according to claim 19 or 20, wherein said  
15 first radio network controller (3-1) comprises a receiving means (10) for receiving a load request transmitted by a transmitting means (20) of said second radio network controller (3-2), wherein said determination means (11) is arranged  
20 to control said transmitting means (10) of said first radio network controller (3-1) to transmit said load information when said load request has been received by said receiving means (10).

22. A system according to claim 21, wherein said determination  
25 means (11) is arranged to periodically determine said load information and to control said transmitting means (10) of said first radio network controller (3-1) to periodically transmit said load information.

30

23. A system according to any one of claims 19 to 22, wherein said determination means (11) is arranged to deter-

mine said load information on the basis of a load parameter received by said first radio network controller (3-1) from a base station (2-1) of said radio cell (13).


5 24. A system according to any one of claims 17 to 23, wherein said mobile radio network is a radio access network of the UMTS.


25. A system according to claim 17, wherein said load  
10 status is used for deciding on an amount of capacity which can be allocated to a user.


26. A system according to claim 17, wherein said load  
status is used for deciding when to order a mobile terminal  
15 controlled by said second radio network controller (3-2) to switch to a dedicated channel state.

27. A system according to claim 26, wherein said mobile  
terminal is ordered to switch to said dedicated channel,  
20 when said load status indicates an overload of a common channel.

28. A radio network controller used as said first (3-1) or  
second (3-2) radio network controller in a system according  
25 to any one of claims 17 to 27.

**Fig. 1**

**Fig. 2**

**Fig. 3**

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 H04Q7/38 H04Q7/22

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 H04Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 97 41698 A (QUALCOMM INC) 6 November 1997 (1997-11-06)  page 6, line 11 - line 19 page 9, line 29 - page 11, line 14 page 16, line 23 - page 17, line 6 page 17, line 18 - page 18, line 24 ---	1-3,6, 11, 17-19, 21,28
A	WO 98 48530 A (ERICSSON TELEFON AB L M) 29 October 1998 (1998-10-29) page 9, line 17 - page 11, line 28 -----	1-28



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

\* Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search

- 4 August 1999

Date of mailing of the international search report

18/08/1999

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Pecci, R

# INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/EP 98/07932

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
WO 9741698 A	06-11-1997	AU 2823597 A CA 2253379 A EP 0896778 A	19-11-1997 06-11-1997 17-02-1999
WO 9848530 A	29-10-1998	AU 7094798 A	13-11-1998

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**